

EPIX360™ TruElectrostatic™ Sprayer Quick Start Guide

CONTENTS: After unpacking, inspect the components for any damage or missing hardware pieces, etc. The following components are included with your purchase:

- 1) TruElectrostatic™ Sprayer
- 2) 14.4v Rechargeable Battery (2)
- 3) 14.4v Battery Charger
- 4) Tank (includes the Tank, Tank liner with Cap Washer, Tank Cap with Filter, & Tank Cap Cover)
- 5) Tank Liner (4 extras included)



Assembled Unit


Step 1: Installing and Removing the Battery

- For best results, make sure the battery is fully charged.
- To check charge, press down on the battery indicator light, the indicator will illuminate 3 green bars when battery is fully charged.
- To install, slide the battery pack onto the bottom of the EPIX360™ handle until the battery pack is firmly seated.
- To remove, grasp battery pack firmly, depress battery pack button down, and slide out from the EPIX360™ USB power source.




Step 2: Liquid Tank Install and Removal

- For the initial set up/test, remove the liquid tank from the sprayer by holding the tank cap cover and the tank, gently rocking it side to side while pulling upwards (A).
- To install the liquid tank into the sprayer, align the tank nozzle to the port on the body of the sprayer and gently press the tank until you feel or hear a click as the Tank Lock and Back Clip will engage.




Step 3: Removing and Installing Tank Cap and Cover

- With the tank removed from the system and holding it vertically, pull the tank cap cover straight up (B). No twisting required (twisting will cause damage to the tank cap cover).
- To remove the tank cap, gently twist counterclockwise.
- To install the tank cap, gently twist clockwise, until cap no longer turns. Each cap has a stopper that keeps you from overturning it.
- To install the tank cap cover onto tank cap, simply line the cover up with the opening of the tank cap.



Step 4: Pouring Solution into the Tank

- Once the tank cap and cover are removed, simply pour the diluted or ready to use solution into the already prepared tank and liner.
- Note: A liner will last for 100 hours of use time or up to 3 months.



Step 5: Depress the Trigger Button to Begin Spraying

- Once the system has been filled with solution, you can begin spraying. Depress the trigger button, keeping it held down for entire spray time desired.
- Once trigger is released, the system will turn off.
- The red indicator light at the back of system is the power indicator light. This turns on when you start spraying and will turn off when the button is released. This light indicates the high voltage power supply is charging the liquid droplets.